

# S 61 SX

## SPECIFICATIONS

	U.S.	Metric
Vertical Reach	196' 10"	60.1 m
Horizontal Reach	184' 2"	56.1 m
Below Grade Reach w/ Tip Hose	149' 11"	45.7 m
Pipeline Diameter	4.5 in	112 mm
Boom Type/ Sections	Overhead Roll & Fold/ 4	
Boom Rotation	370 degrees	
Unfolding Height	59' 9"	18.2 m
Outrigger Type- Front	Super X, Hydraulic Extension & Jacking	
Outrigger Type- Rear	Hydraulic Slewing & Jacking	
Outrigger Soil Pressure w/o Dunnage (front/rear)	157/166 psi	10.8/11.4 bar
Outrigger Soil Pressure w/ Dunnage (front/rear)	51/54 psi	3.5/3.7 bar
Outrigger Width, Front	29' 2"	8.9 m
Outrigger Width, Rear	41' 1"	12.5 m
Outrigger Length	37' 9"	11.5 m

## PUMP SPECIFICATIONS

	U.S.	Metric
Theor. Concrete Output	213 cu yds/h	163 cu m/h
Max. Pressure on Concrete	1169 psi	80 bar
Max. Strokes Per Minute	22	
Max. Aggregate size	2.5 in	63.5 mm
Material Cylinder Diameter	10 in	254 mm
Material Cylinder Stroke	98 in	2500 mm
Differential Cylinder Diameter	4.7 in	120 mm
Maximum Oil Flow	158.5 gal/min	600 l/min
Hydraulic Circuitry Type	MPS	
Valve Type	B Rock	

\*Pump specifications are for standard units. Other units are available. Specifications are subject to change without prior notice.

